



Pos.	A (in.)	A (mm)	B (in.)	B (mm)	Pos.	A (in.)	A (mm)	B (in.)	B (mm)
2	.100	2.54	.200	5.08	16	1.500	38.10	1.600	40.64
3	.200	5.08	.300	7.62	17	1.600	40.64	1.700	43.18
4	.300	7.62	.400	10.16	18	1.700	43.18	1.800	45.72
5	.400	10.16	.500	12.70	19	1.800	45.72	1.900	48.26
6	.500	12.70	.600	15.24	20	1.900	48.26	2.000	50.80
7	.600	15.24	.700	17.78	21	2.000	50.80	2.100	53.34
8	.700	17.78	.800	20.32	22	2.100	53.34	2.200	55.88
9	.800	20.32	.900	22.86	23	2.200	55.88	2.300	58.42
10	.900	22.86	1.000	25.40	24	2.300	58.42	2.400	60.96
11	1.000	25.40	1.100	27.94	25	2.400	60.96	2.500	63.50
12	1.100	27.94	1.200	30.48	26	2.500	63.50	2.600	66.04
13	1.200	30.48	1.300	33.02	27	2.600	66.04	2.700	68.58
14	1.300	33.02	1.400	35.56	28	2.700	68.58	2.800	71.12
15	1.400	35.56	1.500	38.10					

SPECIFICATIONS

- Material: Nylon UL94V-2
- Contacts: Copper alloy, 0.64mm square pin
- Contact plating: Tin or gold flash
- Current rating: 2 amps AC/DC
- Voltage rating: 250VAC/DC
- Circuits: 2-28 available

Series	Contacts	Mounting	Plating
FHA-C	XX	XX	XX
Friction lock header, C style	02-28	STR=Straight RA-Right angle RRA=Reverse right angle	TN=Tin GD=Gold

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	04/10/98
				Checked	Lizzy	04/10/98
				Drawn	Tina	04/10/98
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **FHA-C-XX-XX-XX**

Description: .100" friction lock header, type C