







Feed-through terminals RK | Protective earth terminals SL

Screw connection system



- Foot can be snapped on TS 32 and TS 35 DIN rails
- Housing made from polyamide 6.6 UL 94-V2

Connection diagram

SL 4/35	RK 6-10	RK 6-10/35
 M 3	 M 4	 M 4
		
Protective earth terminal 2 connections	Feed-through terminal 2 connections	Feed-through terminal 2 connections

Connection type

Size (L x W x H) mm with TS 32 mm
Size (L x W x H) mm with TS 35 x 7.5 mm

Type

Type colour

Cat. no.

Type colour

Cat. no.

Type colour

Cat. no.

Type colour

Cat. no.

Colours available

Rated specifications acc. to

Rated voltage, V

Rated current, A

Rated wire cross-section, mm² | AWG

Rated impulse voltage, kV | Contamination degree

Plug gauge acc. to EN 60 947-1 | Flamm. class acc. to UL 94

Connection data

Single wire (solid) / Stranded mm²

Stranded/stranded (w/ferrules acc. to DIN 46 228/1) mm²

Contact wire range, mm²

Stripping length, mm

Torque, Nm | Screw

Special connection, mm

Features

Material of insulated housing | Temperature range

Number of cross-connection channels | Test pick-off

Accessories

End plate AP

Cat. no.

Partition plate TW

Cat. no.

Insulation plate TRS

Cat. no.

Cross-connector Q

Cat. no.

Cross-connector Q /Insulated cross-connector QI

Cat. no.

Insulated cross-connection QI

Cat. no.

Cross-connector Q

Cat. no.

Insulated cross-connection QI

Cat. no.

Cross-connector Q

Cat. no.

Insulated cross-connection QI

Cat. no.

Cross-connector Q

Cat. no.

End stop ES

Cat. no.

Test adapter TA

Cat. no.

Screwdriver SDB

Cat. no.

Quick marking PMC SB

Cat. no.

Screw connection

56 x 8 x 47

Qty.

SL 4/35 GNYE

1212.2

100

IEC

UL

cUL

4 | 22-11

8 | 3

A4 | V2

0.2-6 | -

0.2-6 | 0.2-4

0.2-6

12

0.5-1.0 | Slotted M 3

PA 6.6 | -40 to +105°C

1 | 1

Screw connection

48 x 8 x 51.5
48 x 8 x 47

Qty.

RK 6-10 BG

1005.2

100

IEC

UL

CSA

800 | 600 | 600

57 | 65 | 55

10 | 22-8

6 | 3

A5 | V2

0.2-10 | 0.2-10

0.2-10 | 0.2-10

0.2-10

12

1.2 - 2.0 | Slotted M 4

Screw connection

48 x 8 x 47

Qty.

RK 6-10/35 BG

1578.2

100

IEC

CSAus

CSA

800 | 600 | 600

57 | 65 | 55

10 | 22-8

6 | 3

A5 | V2

0.2-10 | 0.2-10

0.2-10 | 0.2-10

0.2-10

12

1.2 - 2.0 | Slotted M 4