

V-EA-Series - UL508 Manual Motor Controller - 1 pole D-Trip



UL508 Listed
E137938




One Pole

Standard Pack: 12


Weight:

0.3A - 32A
1.8kg (3.97 lb.)
40A - 63A
1.98kg (4.37 lb.)




Rated Current	Type/Cat. No.	Approvals
0.3A	1D03UM	UL, SA, VDE, CE
0.5A	1D05UM	UL, SA, VDE, CE
0.75A	1D075UM	UL, SA, VDE, CE
0.8A	NA	
1.0A	1D1UM	UL, SA, VDE, CE
1.6A	1D1.6UM	UL, SA, VDE, CE
2.0A	1D2UM	UL, SA, VDE, CE
2.5A	1D2.5UM	UL, SA, VDE, CE
3.0A	1D3UM	UL, SA, VDE, CE
3.5A	1D3.5UM	UL, SA, VDE, CE
4.0A	1D4UM	UL, SA, VDE, CE
5.0A	1D5UM	UL, SA, VDE, CE
6.0A	1D6UM	UL, SA, VDE, CE
8.0A	1D8UM	UL, SA, VDE, CE
10A	1D10UM	UL, SA, VDE, CE
12A	NA	
12.5A	NA	
13A	1D13UM	UL, SA, VDE, CE
15A	1D15UM	UL, SA, VDE, CE
16A	1D16UM	UL, SA, VDE, CE
20A	1D20UM	UL, SA, VDE, CE
25A	1D25UM	UL, SA, VDE, CE
30A	1D30UM	UL, SA, VDE, CE
32A	1D32UM	UL, SA, VDE, CE
40A	1D40UM	UL, SA, VDE, CE
50A	1D50UM	UL, SA, VDE, CE
60A	1D60UM	UL, SA, VDE, CE
63A	1D63UM	UL, SA, VDE, CE

V-EA-D Trip
0.3A Through 10A Rated Current



V-EA-D Trip
13A Through 63A Rated Current



Voltage Rating	277VAC 0.3-25A: 1 pole - 42VDC 30-60A: 1 pole - 24VDC
Short Circuit Withstand Rating (UL/CSA - Ratings)	0.3-60A (RC): 10kA with UL-listed RK5 back-up fuse or MCCB
Group Short Circuit Withstand Rating (UL/CSA - Ratings)	0.3-10A (RC): 10kA; 13-60A (RC): 5kA no branch circuit protection required
Interrupting Capacity (VDE - Ratings)	0.3-63A (RC): 10kA
Calibration Temperature	40°C (104°F)
Operating Temperature	-25°C to 55°C (-13°F to 131°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Terminal Size Acceptability	Top: 18-3 AWG; Bottom: 18-2 AWG (Line/Load reversible)
Terminal Torque	20 lb.in.
Terminal Protection Degree	IP20

SHORT CIRCUIT WITHSTAND RATINGS FOR V-EA MANUAL MOTOR CONTROLLER

Trip Curve	Amp Range	Backup Protection	UL-Listed RK5-Fuse up to 10kA	UL-Listed MCCB up to 10kA	No BCP Required up to:
all	0.3 - 10A		4xRC* min 15A, max 70A	4xRC* min 15A, max 70A	10kA
all	12 - 30/32A		4xRC* max 125A	4xRC* max 125A	5kA
all	40 - 50A		4xRC* max 200A	4xRC* max 200A	5kA
all	60 / 63A		4xRC* max 250A	4xRC* max 250A	5kA

*up to nearest rated current

Standard Dual Connection Terminal

All parts are ring tongue compatible.

