

V-EA-Series - UL508 Manual Motor Controller - 2 pole G-Trip



UL508 Listed
E137938



Two Pole

Standard Pack: 6



Weight:

0.3A - 32A

1.8kg (3.97 lb.)


40A - 63A

1.98kg (4.37 lb.)




Rated Current	Type/ Cat. No.	Approvals
0.3A	2G03UM	UL SA
0.5A	2G05UM	UL SA
0.75A	NA	
0.8A	2G08UM	UL SA
1.0A	2G1UM	UL SA
1.6A	2G1.6UM	UL SA
2.0A	2G2UM	UL SA
2.5A	2G2.5UM	UL SA
3.0A	2G3UM	UL SA
3.5A	2G3.5UM	UL SA
4.0A	2G4UM	UL SA
5.0A	2G5UM	UL SA
6.0A	2G6UM	UL SA
8.0A	2G8UM	UL SA
10A	2G10UM	UL SA
12A	2G12UM	UL SA
13A	2G13UM	UL SA
15A	2G15UM	UL SA
16A	2G16UM	UL SA
20A	2G20UM	UL SA
25A	2G25UM	UL SA
30A	2G30UM	UL SA
32A	2G32UM	UL SA
40A	2G40UM	UL SA
50A	2G50UM	UL SA
60A	2G60UM	UL SA
63A	2G63UM	UL SA

V-EA-G Trip 0.3A Through 10A Rated Current



V-EA-G Trip 12A Through 63A Rated Current



Voltage Rating	480Y/277VAC 0.3-25A: 1 pole - 42VDC; 2 Pole - 80VDC 30-60A: 1 pole - 24VDC; 2 Pole - 60VDC
Short Circuit Withstand Rating (UL/CSA - Ratings)	0.3-60A (RC): 10kA with UL-listed RK5 back-up fuse or MCCB
Group Short Circuit Withstand Rating (UL/CSA - Ratings)	0.3-10A (RC): 10kA; 13-60A (RC): 5kA no branch circuit protection required
Interrupting Capacity (VDE - Ratings)	0.3-63A (RC): 10kA
Calibration Temperature	40°C (104°F)
Operating Temperature	-25°C to 55°C (-13°F to 131°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Terminal Size Acceptability	Top: 18-3 AWG; Bottom: 18-2 AWG (Line/Load reversible)
Terminal Torque	20 lb.in.
Terminal Protection Degree	IP20

SHORT CIRCUIT WITHSTAND RATINGS FOR V-EA MANUAL MOTOR CONTROLLER

Trip Curve	Amp Range	Backup Protection	UL-Listed RK5-Fuse up to 10kA	UL-Listed MCCB up to 10kA	No BCP Required up to:
all	0.3 - 10A		4xRC* min 15A, max 70A	4xRC* min 15A, max 70A	10kA
all	12 - 30/32A		4xRC* max 125A	4xRC* max 125A	5kA
all	40 - 50A		4xRC* max 200A	4xRC* max 200A	5kA
all	60 / 63A		4xRC* max 250A	4xRC* max 250A	5kA

*up to nearest rated current

Standard Dual Connection Terminal

All parts are ring tongue compatible.

