

M-G55



Insulating housing, IP55, with PE(N) terminal

MASTERDATA

Item type

GTIN

Manufacturer number

Model

Content unit

Product

4011721176789

M-G55

M-G55

Piece

Order unit	Piece
Content quantity	1 Piece
Price quantity	1
Min. order quantity	1 Piece
Order step	1 Piece
Country of origin	SI
Customs tariff number	85389099

DESCRIPTION

The IP55 insulated housing is suitable for the MS motor circuit breaker and has an integrated PE(N) terminal. There are two pre-stamped cable inlets each at the top and bottom.

FEATURES

ETIM-7.0: Empty enclosure for switchgear (EC000712)

Material housing	Plastic
Width	80 mm
Height	150 mm
Depth	97.2 mm
With transparent cover	No
Suitable for emergency stop	Yes
Model	Surface mounting
Degree of protection (IP)	IP55
Degree of protection (NEMA)	Other

INSULATED ENCLOSURES FOR MOTOR PROTECTIVE CIRCUIT BREAKERS



INSULATED ENCLOSURE IP55

with integrated PE(N) terminal top and bottom each 2xM25 metric knock-outs

ITEM NO.	WEIGHT G / EACH	PU
M-G55	222	1



INSULATED FLUSH MOUNTING ENCLOSURE IP55

with integrated PE(N) terminal

ITEM NO.	WEIGHT G / EACH	PU
M-F55	150	1

ACCESSORIES FOR INSULATED ENCLOSURES M-G55 / M-F55



EMERGENCY-STOP BUTTON

latching, turn to release red, on yellow surface

ITEM NO.	WEIGHT G / EACH	PU
M-PV	40	1



PADLOCKING FACILITY

for up to three padlocks

ITEM NO.	WEIGHT G / EACH	PU
M-VS	95	1



INDICATOR LIGHT

with glow bulb, nominal rated voltage 250 V

COLOUR	ITEM NO.	WEIGHT G / EACH	PU
green	M-SLG2	175	25



INDICATOR LIGHT

with glow bulb, nominal rated voltage 400 V

COLOUR	ITEM NO.	WEIGHT G / EACH	PU
green	M-SLG3	175	25

Max. assembly of insulated enclosures

ITEM NO.	MS	HMS	AM/UM/EHM	M-PV/M-VS	M-SLG
M-G55	1	2	1	1	1
M-F55	1	2	1	1	1